



**CENTURY SERIES POWER PAKS (FOR POLY COOLANT LINES)**



JOB	
AREA	
ITEM NO.	
MODEL NO.	

<b>MODELS</b>
PP50C Series
PP150C Series
PP300C Series



**Perlick Features**

- 1/5, 1/3 and 1/2 HP 115-volt models.
- 134a, constant pressure expansion valve.
- High efficiency, compact heat exchanger.
- Deck-mounted, closed-coupled pump and 1/4 HP motor assembly for easy service.
- Factory pre-mixed glycol guarantees performance.
- Self-Priming 70 gallon per hour glycol pump.
- Galvanized exterior.

Horsepower	Length of Run
1/5	50 feet
1/3	150 feet
1/2	300 feet



**PP SERIES POWER PAKS (FOR POLY COOLANT LINES)**

MODEL NOS.	PP50C	PP150C	PP300C
COMPRESSOR TYPE	Air-cooled	Air-cooled	Air-cooled
DIMENSIONS: EXTERIOR (mm)*	Length "A"	28" (711)	28" (711)
	Width "B"	21-3/4" (553)	21-3/4" (553)
	Height "C"	16-3/4" (416)	16-3/4" (416)
*Allow a minimum of two inches of clearance on the louvered ends of the cabinet for proper air flow. Allow accessibility room on top and front of cabinet for serviceability.			
CONDENSING UNIT H.P.	1/5 H.P.	1/3 H.P.	1/2 H.P.
PUMP (70GPH/80SIG)	Positive Displacement	Positive Displacement	Positive Displacement
SHIPPING WEIGHT LBS (kg)	105 (48)	120 (55)	125 (57)
MAXIMUM FOOTAGE IN THE SYSTEM	50 ft.	150ft.	300 ft
GLYCOL CONCENTRATION	33%	33%	33%
EVAPORATING RATING @ 20°F (BTUH)	1600	2550	3800
REFRIGERANT CHARGE (grams)	4.5oz/128g	10.0oz/284g	10.0z/284g
ELECTRICAL AMPS	5.3	10.5	12.5
ELECTRICAL	120V, 60Hz 1Ph AC- Furnished with Three Prong, Six Foot Cord		
REFRIGERATION	134a, Constant Pressure Expansion Valve, Condensing unit with service valves.		
PLUMBING	None required		
CABINET	Galvanized		
OPTIONAL ACCESSORIES	<ul style="list-style-type: none"> <li>C214499BSS Stainless steel power pak stand</li> <li>WB08 Wall bracket</li> </ul>		

