

Мо	dels
4066-6L	4066-6R
4066-8L	4066-8R
4066-10L	4066-10R
4066-12	

The **Polished Brew Pipe Tower** makes a statement in a variety of settings, including both modern and rustic venues. Solid metal construction ensures years of durability, while the superior insulation and cooling technology deliver the perfect pour.

KEY PRODUCT FEATURES AND BENEFITS

- Robust pipes and flanges are durable and offer an industrial feel that makes a statement in the space
- Pure copper coolant lines and cold block maintain chilled beverage temperature, minimizing foam and lost profits
- Insulated dispensing head and shank bushings minimize sweating to keep your bar clean, cool more efficiently for energy reduction, and reduce warm spots in the tower to give you the perfect pour
- 304 stainless steel shanks ensure purity of flavor from keg to tap

Quick Features:

- Available with 6, 8, or 10 faucets with lines leading left or right
- Available with 12 faucets, lines leading both ways
- Faucets and tap handles sold separately

ACCESSORIES

MODEL NOS.	DESCRIPTION
630SS	Stainless Steel Forward Sealing Faucet
650SS	Stainless Steel Forward Sealing Faucet w/ Flow Control
680SS	Stainless Steel Faucet with Push-back Creamer
690SS	Stainless Steel Flow Control Faucet with Push-back Creamer
63927	Stout and Ale faucet - Stainless steel body and spout
308-40C	Beer faucet lock for 630 Series Faucets
67141	Perlick Pub handle - 7-1/2" wooden handle

^{*} Faucets sold separately

Form No. Z2398 Rev. 02.13.23

BREW PIPE TOWERS - POLISHED CHROME

POLISHED CHROME BREW PIPE TOWER

NUMBER OF FAUCETS		6	8	10	12
	Beer Leads Left	4066-6L	4066-8L	4066-10L	-
MODEL NUMBERS	Beer Leads Right	4066-6R	4066-8R	4066-10R	-
	Beer Leads Left and Right				4066-12
"A", LENGTH (MM)		38-1/8" (968)	44-1/8" (1121)	50-1/16" (1272)	56-1/16" (1424)
"B", HEIGHT (MM)		17-1/2" (445)	17-1/2" (445)	17-1/2" (445)	17-1/2" (445)
"C", CENTER T	O CENTER (MM)	32-1/4" (819)	38-1/4" (972)	44-1/4" (1124)	50-1/4" (1276)
FAUCET CENT	ERS (MM)	3" (76)	3" (76)	3" (76)	3" (76)
SHIPPING WE	IGHT, LBS. (KG)	101 (45)	107 (48)	133 (60)	149.5 (67)
OPTIONAL D	RIP PAN	C18750	C18750-27	C18750-33	C18750-39

