

The industrial aesthetic of the *Brew Pipe Tower* makes a statement in a variety of settings, including both modern and rustic venues. Solid metal construction ensures years of durability, while the superior insulation and cooling technology deliver the perfect pour.

## **KEY PRODUCT FEATURES AND BENEFITS**

- Robust pipes and flanges are durable and offer an industrial feel that makes a statement in the space
- Pure copper coolant lines and cold block maintain chilled beverage temperature, minimizing foam and lost profits
- Insulated dispensing head and shank bushings minimize sweating to keep your bar clean, cool more efficiently for energy reduction, and reduce warm spots in the tower to give you the perfect pour
- 304 stainless steel shanks ensure purity of flavor from keg to tap

## **Quick Features:**

- T-Shape available with 6-12, and 16 faucets even faucet counts only
- Additional faucet configurations available with the L-Shape or Pass-Thru Brew Pipe Towers
- Installation bolt required; kits sold separately
- Faucets and tap handles sold separately

## ACCESSORIES

MODEL NOS.	DESCRIPTION			
630SS	Stainless Steel Forward Sealing Faucet			
650SS	Stainless Steel Forward Sealing Faucet w/ Flow Control			
680SS	Stainless Steel Faucet with Push-back Creamer			
690SS	Stainless Steel Flow Control Faucet with Push-back Creamer			
63927	927 Stout and Ale faucet - Stainless steel body and spout			
308-40C	Beer faucet lock for 630 Series Faucets			
67141	Perlick Pub handle - 7-1/2" wooden handle			

\* Faucets sold separately



BREW PIPE TOWERS

## **TEE SHAPE TOWER**

NUMBER OF FAUCETS		6	8	10	12	16
MODEL NUMBERS		4061-6	4061-8	4061-10	4061-12	4061-16
FAUCET CENTERS (MM)		3″ (76)	3″ (76)	3″ (76)	3″ (76)	3″ (76)
"A", LENGTH (MM)		31-5/16" (795)	37-5/16" (948)	43-1/4" (1099)	49-1/4" (1251)	61-1/4" (1556)
"B", STANDARD HEIGHT (MM)		17-3/4" (451)	17-3/4" (451)	17-3/4" (451)	17-3/4" (451)	17-3/4" (451)
SHIPPING WEIGHT, LBS. (KG)		101 (46)	117 (53)	133 (60)	149 (68)	179.5 (81)
OPTIONAL DRIP PAN	MODEL NUMBER	7020-32	7020-38	7020-44	7020-50	7020-62
	"A", LENGTH (MM)	32" (813)	38" (965)	44" (1118)	50" (1270)	62" (1575)
	"B", DEPTH (MM)	10" (254)	10" (254)	10" (254)	10" (254)	10″ (254)

5/8" mounting bolt kits required

