









JOB	
AREA	
ITEM NO.	
MODEL NO.	





Glass Door Model

Solid Door Model

MODELS	DESCRIPTION	
HC24BB-4-1R/L	Indoor C-Series Beverage Center Solid Stainless Steel Door	
HC24BB-4-2R/L	Indoor C-Series Beverage Center Solid Panel Ready Door	
HC24BB-4-3R/L	Indoor C-Series Beverage Center Stainless Steel Glass Door	
HC24BB-4-4R/L	Indoor C-Series Beverage Center Panel Ready Glass Door	

## **KEY PRODUCT FEATURES AND BENEFITS**

- Superior construction provides ideal combination of energy efficient operation & powerful refrigeration performance ideal for food and beverages
- 800 BTU/hr capacity delivers commercial grade cooling performance
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning; black vinyl exterior for built in applications
- Wine and refrigerator shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time

## **Quick Features:**

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 62 cans and 16 bottles of wine



MODEL NUMBERS		HC24BB	
MODEL DESCRIPTION		24" Indoor Beverage Center	
ATTRIBUTES			
Perlick Anti-Condensation System		NO	
Energy Star Certified		YES	
	Width - in. (mm)	23-7/8" (606 mm.)	
OVERALL DIMENSIONS	Depth - in. (mm)	24" (610 mm.)	
	Height - in. (mm)	34-1/4" (870 mm.)	
	Width - in. (mm)	24" (610 mm.)	
STANDARD OPENING DIMENSIONS	Depth - in. (mm)	24-7/8" (632 mm.)	
	Height - in. (mm)	34-1/2" (876 mm.)	
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.	
SHIPPING WEIGHT Lbs. (kg.)		195 lbs (88.45 kg.)	
	Electrical Supply	115 VAC/60 Hz/1 Ph	
	Running Load Amps	2.2 amps	
	Electrical Connection	Cord connected	
	Cord Plug Type	NEMA 3 Prong 5-15P	
ELECTRICAL SPECIFICATIONS	Cord Length	6′	
	Defrost Initiation	Automatic	
	Defrost Type	Off cycle	
	Thermostat	Digital	
	Lighting Type	LED	
	Refrigerant	R600a (50g)	
REFRIGERATION SPECIFICATIONS	Expansion Device	Capillary Tube	
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	
	Heat Rejection (at 75°F)	450 BTU/hr	
	Pull Down Capacity	800 BTU/hr	
	Front Vented	Yes	
PLUMBING		None Required	

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

## **ACCESSORIES**

MODEL NOS.	DESCRIPTION	
(L)	Factory Installed Lock	
66736	Caster Kit for HP24/HC24/HA24 models	
RS-24-24D	Divider Shelf for HP24/HC24/HA24 models	

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.



## WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about Prop 65, go to **P65Warnings.ca.gov**.



CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HC24BB-4-1L	HC24BB4C-00-SLS0B	Left	No
HC24BB-4-1R	HC24BB4C-00-SRS0B	Right	No
HC24BB-4-2L	HC24BB4C-00-PL00B	Left	No
HC24BB-4-2R	HC24BB4C-00-PR00B	Right	No
HC24BB-4-3L	HC24BB4C-00-TLS0B	Left	No
HC24BB-4-3R	HC24BB4C-00-TRS0B	Right	No
HC24BB-4-4L	HC24BB4C-00-RL00B	Left	No
HC24BB-4-4R	HC24BB4C-00-RR00B	Right	No
HC24BB-4-1LL	HC24BB4C-00-SLSLB	Left	Yes
HC24BB-4-1RL	HC24BB4C-00-SRSLB	Right	Yes
HC24BB-4-2LL	HC24BB4C-00-PL0LB	Left	Yes
HC24BB-4-2RL	HC24BB4C-00-PR0LB	Right	Yes
HC24BB-4-3LL	HC24BB4C-00-TLSLB	Left	Yes
HC24BB-4-3RL	HC24BB4C-00-TRSLB	Right	Yes
HC24BB-4-4LL	HC24BB4C-00-RL0LB	Left	Yes
HC24BB-4-4RL	HC24BB4C-00-RR0LB	Right	Yes





