



**15" SIGNATURE SERIES**  
Beverage Dispenser - Draft Arm Tower



**eco friendly**  
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Solid Door Model



**650SS Forward Sealing Flow Control Beer Faucet**

MODELS	DESCRIPTION
<b>HP15TS-4-1L/R-1</b>	Indoor Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
<b>HP15TS-4-2L/R-1</b>	Indoor Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet
<b>HP15TO-4-1L/R-1</b>	Outdoor Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
<b>HP15TO-4-2L/R-1</b>	Outdoor Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet
<b>HP15TM-4-1L/R-1</b>	Marine Signature Series Beverage Dispenser Solid Stainless Steel Door 1 Faucet
<b>HP15TM-4-2L/R-1</b>	Marine Signature Series Beverage Dispenser Solid Panel Ready Door 1 Faucet

**KEY PRODUCT FEATURES AND BENEFITS**

- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (Outdoor and Marine models only)
- Marine & Coastal Grade with Perlick Armor™ upgrades stainless steel, fasteners, and refrigeration system to the highest blend of corrosion resistance and food safety

**Quick Features:**

- Forced air refrigeration technology ensures consistent temperature throughout entire keg maintaining flavor better than other brands
- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Accommodates one (1) 1/6 barrel



One 1/6 barrel



**15" SIGNATURE SERIES**  
*Beverage Dispenser - Draft Arm Tower*

MODEL NUMBERS		HP15TS	HP15TO	HP15TM
<b>MODEL DESCRIPTION</b>		15" Indoor Beverage Dispenser - Draft Arm Tower	15" Outdoor Beverage Dispenser - Draft Arm Tower	15" Marine Beverage Dispenser - Draft Arm Tower
<b>ATTRIBUTES</b>				
<b>Perlick Anti-Condensation System</b>		NO	YES	YES
<b>Perlick Armor™</b>		NO	NO	YES
<b>OVERALL DIMENSIONS</b>	<b>Width - in. (mm)</b>	14-7/8" (378 mm.)	14-7/8" (378 mm.)	14-7/8" (378 mm.)
	<b>Depth - in. (mm)</b>	24" (610 mm.)	24" (610 mm.)	24" (610 mm.)
	<b>Height - in. (mm)</b>	34-1/4" (870 mm.)	34-1/4" (870 mm.)	34-1/4" (870 mm.)
<b>STANDARD OPENING DIMENSIONS</b>	<b>Width - in. (mm)</b>	15" (381 mm.)	15" (381 mm.)	15" (381 mm.)
	<b>Depth - in. (mm)</b>	24-7/8" (632 mm.)	24-7/8" (632 mm.)	24-7/8" (632 mm.)
	<b>Height - in. (mm)</b>	34-1/2" (876 mm.)	34-1/2" (876 mm.)	34-1/2" (876 mm.)
<b>INTERNAL VOLUME Net. Cu. Ft.</b>		2.8 cu. ft.	2.8 cu. ft.	2.8 cu. ft.
<b>SHIPPING WEIGHT Lbs. (kg.)</b>		144 lbs (100.7 kg.)	144 lbs (100.7 kg.)	144 lbs (100.7 kg.)
<b>ELECTRICAL SPECIFICATIONS</b>	<b>Electrical Supply</b>	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	<b>Running Load Amps</b>	1.7 amps	1.7 amps	1.7 amps
	<b>Electrical Connection</b>	Cord connected	Cord connected	Cord connected
	<b>Cord Plug Type</b>	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	<b>Cord Length</b>	6'	6'	6'
	<b>Defrost Initiation</b>	Automatic	Automatic	Automatic
	<b>Defrost Type</b>	Off cycle	Off cycle	Off cycle
	<b>Thermostat</b>	Digital	Digital	Digital
	<b>Lighting Type</b>	LED	LED	LED
<b>REFRIGERATION SPECIFICATIONS</b>	<b>Refrigerant</b>	R600a (44g)	R600a (44g)	R600a (44g)
	<b>Expansion Device</b>	Capillary Tube	Capillary Tube	Capillary Tube
	<b>Temperature Settings F°(C°)</b>	33° (0.5°) - 48° (8.8°) <b>Factory Set Point 36° (2.2°)</b>	33° (0.5°) - 48° (8.8°) <b>Factory Set Point 36° (2.2°)</b>	33° (0.5°) - 48° (8.8°) <b>Factory Set Point 36° (2.2°)</b>
	<b>Heat Rejection (at 75°F)</b>	300 BTU/hr	300 BTU/hr	300 BTU/hr
	<b>Pull Down Capacity</b>	1000 BTU/hr	1000 BTU/hr	1000 BTU/hr
	<b>Front Vented</b>	Yes	Yes	Yes
<b>PLUMBING</b>		None Required	None Required	None Required

*Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.*

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736-15	Caster Kit for HP15 models
63797	Beer Dispenser Cleaning Kit
400305	Keg Coupler, Lo-Boy "S" Series
67141-1	Perlick Faucet Handle
BLC4/32	Beer Dispenser Sanitizer (4oz. or 32 oz.)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit [perlick.com](http://perlick.com).



**15" SIGNATURE SERIES**  
*Beverage Dispenser - Draft Arm Tower*

	CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
INDOOR	HP15TS-4-1L-1	HP15TS4C-B0-SLF0T	Left	No
	HP15TS-4-1R-1	HP15TS4C-B0-SRF0T	Right	No
	HP15TS-4-2L-1	HP15TS4C-B0-PL00T	Left	No
	HP15TS-4-2R-1	HP15TS4C-B0-PR00T	Right	No
	HP15TS-4-1LL-1	HP15TS4C-B0-SLFLT	Left	Yes
	HP15TS-4-1RL-1	HP15TS4C-B0-SRFLT	Right	Yes
	HP15TS-4-2LL-1	HP15TS4C-B0-PLOLT	Left	Yes
	HP15TS-4-2RL-1	HP15TS4C-B0-PROLT	Right	Yes
OUTDOOR	HP15TO-4-1L-1	HP15TO4C-B0-SLF0T	Left	No
	HP15TO-4-1R-1	HP15TO4C-B0-SRF0T	Right	No
	HP15TO-4-2L-1	HP15TO4C-B0-PL00T	Left	No
	HP15TO-4-2R-1	HP15TO4C-B0-PR00T	Right	No
	HP15TO-4-1LL-1	HP15TO4C-B0-SLFLT	Left	Yes
	HP15TO-4-1RL-1	HP15TO4C-B0-SRFLT	Right	Yes
	HP15TO-4-2LL-1	HP15TO4C-B0-PLOLT	Left	Yes
	HP15TO-4-2RL-1	HP15TO4C-B0-PROLT	Right	Yes
MARINE & COASTAL	HP15TM-4-1L-1	HP15TM4C-B0-MLF0T	Left	No
	HP15TM-4-1R-1	HP15TM4C-B0-MRF0T	Right	No
	HP15TM-4-2L-1	HP15TM4C-B0-PL00T	Left	No
	HP15TM-4-2R-1	HP15TM4C-B0-PR00T	Right	No
	HP15TM-4-1LL-1	HP15TM4C-B0-MLFLT	Left	Yes
	HP15TM-4-1RL-1	HP15TM4C-B0-MRFLT	Right	Yes
	HP15TM-4-2LL-1	HP15TM4C-B0-PLOLT	Left	Yes
	HP15TM-4-2RL-1	HP15TM4C-B0-PROLT	Right	Yes



**15" SIGNATURE SERIES**  
*Beverage Dispenser - Draft Arm Tower*

