

Perlick® 24" GLASS CHILLER

eco friendly
R600a Refrigerant



5 Year
Compressor
Warranty



JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODEL NO.
HC24FS-BS-STK



HC24FS-BS-STK

KEY PRODUCT FEATURES AND BENEFITS

- All stainless steel interior ensures consistent cabinet temperature and hygienic easy to clean environment that will not absorb odors over time
- Full extension, smooth glide shelving gives easy access to product and faster, more ergonomic product loading
- Ultra-quiet and energy efficient smart compressor – compressor ramps up as additional cooling is needed maximizing energy savings while decreasing pull down time
- NSF rated digital controller allows for precision temperature setting and features and audible door alarm, alerting the operator if an intrusion will not allow the door to close
- Open shelf design allows cold air to surround product reducing temperature variation in the cabinet and extending product life
- 525 BTU/hr fast pull down of product to serving temperature

Quick Features:

- 2" foamed-in-place eco-friendly insulation provides energy savings with zero ozone depletion
- Smart defrost cycle runs only when needed, increasing energy efficiency over standard systems
- Selectable white or blue LEDs provide crisp line of sight to product
- Black vinyl door panel can easily be removed to allow a custom wood overlay to be applied
- Custom door are customer supplied – see perlick.com for door overlay templates
- Field reversible door allows for easy replacement or re-purposing
- Door lock standard to secure contents
- NSF 7 rated for canned and bottle beverage storage
- No plumbing required
- 1 Year Warranty, 5 Year Compressor Warranty



24" GLASS CHILLER

MODEL NO.		HC24FS-BS-STK
CABINET DIMENSIONS	Length Ins. (mm)	23-7/8" (606)
	Depth Ins. (mm)	24" (610)
	Height Ins. (mm)	34" (864)
SHIP WEIGHT LBS. (KG)		195 (88)
CAPACITY CU. FT. (L.) [PRODUCT*]		5.3 (150) [86 glasses]
SHELVING		2 black vinyl-coated full-extension shelf (adjustable)
TEMPERATURE SETTINGS F°(C°)		-10° (-23.3°) - 10° (-12.2°) Factory Set Point 0° (-17.8°)
CABINET CONSTRUCTION (INT.)		Interior Stainless Steel
CABINET CONSTRUCTION (EXT.)		Exterior Sides, Exterior Top and Grill Stainless Steel Exterior Back and Exterior Bottom Galvanized
CABINET INSULATION		Polyurethane-Ecomate. Wall Thickness 2" Door, Drawer Thickness 2" (solid stainless steel only)
DOORS, HINGING & HARDWARE		Number of Doors 1 Opening Style Hinged Left Door Style Solid Door Swing Clearance 25" (635)
CONDENSING UNIT		Condenser Access Front
REFRIGERATION		Refrigerant R600a: 62g Expansion Device Capillary Tube Type w/Hermetic Compressor Defrost Automatic 4-hour hot gas defrost cycle
HEAT REJECTION (at 75°F ambient)		700 BTU/hr
PULL DOWN CAPACITY		525 BTU/hr
PLUMBING		None required. Moisture drains to self evaporating condensate pan
ELECTRICAL		Electrical Supply 115V/60 Hz/1 Phase Running Load Amps 1.9 Cord Connection Cord Connected (3-prong 6' NEMA 5-15P) Thermostat Digital Lighting Type LED
VENTILATION		Front-vented
ADDITIONAL ACCESSORIES		Casters 3.75" (Part No. 66736) Legs 4"-5" (Part No. 66734), 6"-7.25" (Part. No 66735)

*Product capacity based on 3" diameter glass size

NOTE: This equipment is intended for the storage and display of non-potentially hazardous bottled or canned products only!

! WARNING: California Prop 65 Notice

These products may expose you to chemicals including Chromium, which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information on whether a product in this list contains these chemicals, please refer to the specific product page at perlick.com. Or to find out more about Prop 65, go to P65Warnings.ca.gov.



24" GLASS CHILLER

