



15" SIGNATURE SERIES
Adara Beverage Dispenser



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Solid Door Model



650SS Forward Sealing Flow Control Beer Faucet

MODELS	DESCRIPTION
HP15TS-4-1L/R-1A	Indoor Signature Series Adara Beverage Dispenser Solid Stainless Steel Door 1 Faucet
HP15TS-4-2L/R-1A	Indoor Signature Series Adara Beverage Dispenser Solid Panel Ready Door 1 Faucet

KEY PRODUCT FEATURES AND BENEFITS

- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning

Quick Features:

- Forced air refrigeration technology ensures consistent temperature throughout entire keg, maintaining flavor better than other brands
- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- White LED task lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Accommodates one (1) 1/6 barrel



One 1/6 barrel



15" SIGNATURE SERIES
Adara Beverage Dispenser

MODEL NUMBERS		HP15TS
MODEL DESCRIPTION		15" Indoor Beverage Dispenser - Adara Tower
ATTRIBUTES		
Perlick Anti-Condensation System		NO
OVERALL DIMENSIONS	Width - in. (mm)	14-7/8" (378 mm.)
	Depth - in. (mm)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	15" (381 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		2.8 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		144 lbs (100.7 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.7 amps
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (44g)
	Expansion Device	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	300 BTU/hr
	Pull Down Capacity	1000 BTU/hr
	Front Vented	Yes
PLUMBING		None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736-15	Caster Kit for HP15 models
63797	Beer Dispenser Cleaning Kit
40030S	Keg Coupler, Lo-Boy "S" Series
67141-1	Perlick Faucet Handle
BLC4/32	Beer Dispenser Sanitizer (4oz. or 32 oz.)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.

15" SIGNATURE SERIES

Adara Beverage Dispenser

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HP15TS-4-2L-1A	HP15TS4C-E0-PL00T	Left	No
HP15TS-4-2R-1A	HP15TS4C-E0-PR00T	Right	No
HP15TS-4-1LL-1A	HP15TS4C-E0-SLFLT	Left	Yes
HP15TS-4-1RL-1A	HP15TS4C-E0-SRFLT	Right	Yes
HP15TS-4-2LL-1A	HP15TS4C-E0-PL0LT	Left	Yes
HP15TS-4-2RL-1A	HP15TS4C-E0-PR0LT	Right	Yes

